

E O S

AccuLite[®]
Commercial and Industrial Lighting

Adjustable angle wall mounted
security lighting



MODUL
ELECTRO
www.modulelectro.ru


JUNO LIGHTING GROUP
by Schneider Electric

Eos™ Aimable Wall Sconce

Robust construction, high precision optics, and energy efficiency all come together seamlessly in Eos™ adjustable wall luminaires. Featuring a two piece adjustable angle design, Eos™ can be installed as a full cutoff fixture or aimed at an angle of up to 30° without the need to access the interior of the fixture. The aiming adjustment allows the installer to fit the same fixture to different functions right at the job site.



WAM:
Aimed Down

WAM:
Aimed out 30°

MODULO
ELECTRO

www.modulelectro.ru

Aimable Optics

Cast-in scale on the outside of the housing makes aiming from 0° (nadir) thru 30° fast and easy. Simply loosen the external adjustment knob, aim, then tighten it back up.

Full Cut-Off Optics

When the optic is aimed down (0°), Eos™ is a full cut-off luminaire.

Two Fixture Sizes

Available with metal halide, high pressure sodium and compact fluorescent light sources, Eos™ is offered in two sizes - 26W through 175W and 200W through 400W.

Construction

Housing and optical units are die cast aluminum. Reflectors are specular or hammer tone. Lens is heat and impact resistant tempered glass.

Certification

Suitable for wet locations UL1598/CSA C22.2 No250

Tool Free Servicing

Unique snap action door latch makes re-lamping a one hand operation.

Emergency Circuit

Emergency circuit allows Eos™ to be used for outdoor egress applications. Used when a 120V emergency power source is available.

Finish

Bronze polyester powder coat.

EISA & Pulse Start Metal Halide

AccuLite Pulse Start MH luminaires are designed and built to meet Energy Independence and Security Act (EISA) standards. Pulse Start provides longer lamp life, more lumens per watt, better lumen maintenance, superior color rendering, faster lamp warm up and faster hot restrike.

Mounting

Mounts flush to the wall on 3-1/2" or 4" junction boxes.


Eos™ - Ordering Information

Ordering Information

WAS	42CF	-E2	-WT	-PC	-BZ
Series	Lamp Watts	Ballast Volts	Beam Spread	Options	Color
WAS Small Housing	Compact Fluorescent GX24Q base One lamp 26CF, 32CF, 42CF	Electronic - UN 120V to 277V - E1 120V - E2 277V - E3 347V	- WT Wide throw - FT Forward throw	HID Lamp - L HID Lamp Clear - ED17, B17 - CL Coated - ED17, B17 Compact Fluorescent Lamp By others Photocontrol Replace "-UN", "-QT" and "-TT" with line voltage suffix - PC Maximum 480V Emergency Circuit Quartz Lamp Double contact bayonet base quartz lamp by others - ES Requires 120V emergency power source Quartz Auxiliary For use with HID luminaires Double contact bayonet base quartz lamp by others - Q Cold Start/Hot Restrike - HQ Hot Restrike Fuse - F1 Single pole line to neutral Supplied with fuse Replace multi tap ballast suffixes with line voltage suffix	Housing Color - BZ Bronze
	Compact Fluorescent GX24Q base Two lamps 226CF, 232CF, 242CF	Electronic - UN 120V to 277V - E1 120V - E2 277V - E3 347V	- WT Wide throw		
	Pulse Start Metal Halide 50PS 50W ED17 70PS 70W ED17	Magnetic Ballast QT Quad-Tap, 120/208/240/277V TT Tri-Tap 120/277/347V			
	Pulse Start Metal Halide 100PS 100W ED17 150PS 150W ED17	Magnetic Ballast QT Quad-Tap, 120/208/240/277V TT Tri-Tap 120/277/347V 480 480V			
	Probe Start Metal Halide 175MH 175W ED17 🍁	Magnetic Ballast QT Quad-Tap, 120/208/240/277V TT Tri-Tap 120/277/347V 480 480V	- WT Wide throw - FT Forward throw		
	High Pressure Sodium 35HP (120v only) 35W B17 50HP 50W B17	Magnetic Ballast 120 120V 277 277V 347 347V			
	High Pressure Sodium 70HP 70W B17	Magnetic Ballast QT Quad-Tap 120/208/240/277V TT Tri-Tap 120/277/347V			
	High Pressure Sodium³ 100HP 100W B17 150HP 150W B17	Magnetic Ballast QT Quad-Tap, 120/208/240/277V TT Tri-Tap 120/277/347V 480 480V			
WAM Medium Housing	Compact Fluorescent GX24Q base One lamp 57CF, 70CF	Electronic - UN 120V to 277V - E1 120V - E2 277V - E3 347V			
	Pulse Start Metal Halide† ED28 Mogul base 250PS ⓘ ED37 Mogul base 320PS, 350PS, 400PS ⓘ Probe Start Metal Halide† ED28 Mogul base 250MH 🍁 ED37 Mogul base 400MH 🍁 High Pressure Sodium ED18 Mogul Base 250HP, 400HP	Magnetic Ballast - QT‡ Quad Tap 120V, 208V, 240V, 277V - TT Tri Tap 120V, 277V, 347V	- WT Wide throw - FT Forward throw		

Dimensions

	H	D	W
Small Housing	5-1/2"	16-3/8"	12-7/8"
Medium Housing	7-1/2"	20"	16-7/8"



- † **Metal Halide Lamps:**
- ⓘ EISA: Pulse Start MH lamps meet Energy Independence & Security Act requirements.
- ‡ **Lamp Socket Protector:** Used in Canada with 208V, 240V & 480V line to line circuits - add suffix "-LSP."
- 🍁 Items marked with a red maple leaf are only available in Canada



JUNO LIGHTING GROUP
by Schneider Electric

Juno

Recessed and Trac Lighting

indy

Architectural Recessed Lighting

Alfa

Decorative Lighting Systems

AccuLite

Commercial and Industrial Lighting

AcuLux

Precision Recessed Lighting

Navilite

Exit and Emergency Lighting

DanaLite

Architectural Linear Lighting

MODULO
ELECTRO

www.modulelectro.ru

1300 S. Wolf Road • Des Plaines, Illinois 60018
PHONE (847) 827.9880 • FAX (847) 827.2457 • junolightinggroup.com

Regional Offices & Warehouses:

California, Georgia, Illinois, Indiana, Pennsylvania, Texas, Ontario CN

LIT-ACCU-EOS



AccuLite is a registered trademark of Juno Lighting, LLC.
Products shown in this brochure are covered by U.S. and
international patents and patents pending.
Specifications subject to change without notice.
© 2009 JUNO LIGHTING, LLC.

Printed in the U.S.A. LIT-ACCU-EOS 10/09